

#### **CODE NUMBER**

3375423

#### DESCRIPTION

1.0 gpf, Polished Chrome Finish, Single Flush, Hardwired, ECOS® Exposed Sensor Urinal Retrofit Flushometer.

#### DETAILS

Flush Volume: 1.0 gpf (3.8 Lpf)
Finish: Polished Chrome (CP)
Power Type: Hardwired (HW)

Battery Life: 6 yearsValve: Diaphragm

• Valve Body Material: Semi-red Brass

• Fixture Type: Urinal

• Fixture Connection: Top spud

#### **FEATURES**

- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.



Variations Not Shown: Brushed Stainless and Dual Flush

### **COMPLIANCES & CERTIFICATIONS**





(ADA Compliant, cUPC Certified)

### RECOMMENDED SPECIFICATION

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance with the applicable sections of ASSE 1037 and ANSI/ASME 112.19.2.

### **ELECTRICAL SPECIFICATIONS**

• Battery Life: 6 years

# **VALVE OPERATING PRESSURE (FLOWING)**

15–80 PSI (103–552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

# **DOWNLOADS**

- Sloan ECOS Valve Installation Instructions
- ECOS Single Flush HW Flushometer and Retrofit
- Control Stop Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- ECOS Repair and Maintenance Guide
- ECOS HW Repair and Maintenance Guide
- Additional Downloads

## NOTES

All information contained within this document subject to change without notice.

Looking for other variations of the ECOS RESS-U product? View the general spec sheet with all options.

Find a compatible urinal for this flushometer.
Find a compatible water closet for this flushometer.

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com



## **ROUGH-IN**

